





- Notes:**
1. Discharge positions viewed from the drive end.
  2. Consult factory for other discharge positions.

### PUMP DIMENSIONS

Model	Frame	Connection		A	B	C	D	DD	E	H	L	M	MA	MB
		Disch.	Suct.											
12NHPP	F12	12	12	14.5	3	50.53	5.62	26.62	6	0.88	39.16	47.61	22.97	22.64

### PUMP DIMENSIONS *(continued)*

N	O	P	Q	R	S	U	V	W	X	Y	Z	KEYWAY
1.25	54.5	1.25	2	28.28	3.5	2.88	6.5	9	32	1.25	18.62	.75 X .38

- Notes:**
1. Dimension "Q" is maximum adjustment for field weld.
  2. "V" dimension is maximum useable shaft.
  3. Frame mounting foot thickness is .75".
  4. Dimension "DD", "M", "MA", and "R" shown are for top vertical position only.
  5. Flange connection dimension can vary  $\pm .12$  inch.
  6. Do not use for construction unless certified.

**Cornell Pump Company**  
 P.O. Box 6334  
 Portland, Oregon 97228-6334  
 Web: [www.cornellpump.com](http://www.cornellpump.com)  
 Phone (503) 653-0330 • Fax (503) 653-0338