



CORNELL PUMP COMPANY

APPLICATIONS


OIL & GAS



Ball valve gives provision for bypassing water back to reservoir in low flow situations.



Heavy duty valves installed to handle the high pressure delivered by our MX pumps.



Double suction set up allows for maximum flow to the pump, but also makes for easier handling vs. a 12" line which would be required for the same flows in a single line.

6822MX HIGH HEAD PUMP REPLACES LOWER HEAD WATER TRANSFER PUMP

Saves Money on Energy and Maintenance expenses.

A Gulf Coast-based pump supplier of Cornell, one of the leading suppliers to the shale fracturing industry, had a customer that faced piping hydraulic fracturing water transfer with multiple pumps. New Cornell pumps helped pump more efficiently with lower fuel costs.

The company operated six miles of twin 8" pipeline with 100' of positive elevation change over the length of the channel. The company needed to pump 100 barrels of water per minute (4,200 GPM) through the pipeline to supply the water.

The water transfer company had nine 6NHTBs on site. Three of the 6NHTBs were sitting at the water source. Spaced along the twin 8' pipelines were six more 6NHTBs at intervals. This required significantly more labor to set, maintain and monitor nine pumps than the solution pumps.

After Cornell and the dealer analyzed the specifications for the system, an option was recommended that cut the number of pumps needed to three. The solution was to place an 8NHTH at the water as a supply pump and one 6822MX on each 8" pipeline as a booster pump. Not only did this cut the number of pumps by two-thirds, but it also drastically reduced diesel fuel consumption on the project.

The 6822MX is part of Cornell's high-head "MX" line of mining pumps introduced in 2010. The "MX" line of pumps boasts industry-leading performance with flows up to 8,000 GPM and heads up to 800' TDH. They are available in 2" to 8" discharge charge sizes and include ductile iron castings with CA6NM impellers.

While the 8NHTH is not a new pump for Cornell, it is relatively new to the oilfields. It is a 10X8 pump that boasts a maximum 20.50" impeller with a max flow of 8400 GPM and a shutoff head 460'. This impressively solid pump has a wide flow range with excellent efficiencies.

Since being introduced into the oilfields by the supplier in 2011, the "MX" pumps and the 8NHTH has substantially changed how many of these complex projects are approached. Stacking large numbers of pumps to do long pipe runs or drastic elevation changes is no longer necessary. These pumps have become staples of many oilfield companies' product offerings.